PATENT ABSTRACTS OF JAPAN

(11)Publication number:

58-148507

(43)Date of publication of application: 03.09.1983

(51)Int.CI.

H03F 3/72

(21)Application number: 57-031067

(71)Applicant:

YOKOGAWA HEWLETT PACKARD LTD

(22)Date of filing:

26.02.1982


(72)Inventor:

TAKAGI SHUN

(54) COMPOSITE CONTROLLING AMPLIFIER

(57)Abstract:

PURPOSE: To hold a terminal voltage of a load constantly, by controlling an amplifier to be controlled with a specific controlling amplifier. CONSTITUTION: When an operational amplifier 4 is controlled with a controlling amplifier 2, a saturation preventing current IS1 flows to a controlling amplifier 1' in this state. A prescribed relation exists among the IS1, an input voltage V1 of the amplifier 1' and an output voltage V0. Thus, when a switch SW2 is opened and the control of an operational amplifier 4 with the amplifier 2 is blocked, the control of the controlling amplifier 1' is realized quickly. No spike voltage due to the controlling amplifier switching is generated. Since the operational amplifier 4 is controlled with the amplifier 1' exclusively, the output voltage V0 is unchanged even if voltages VM, V2, and V3 are changed.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

BEST AVAILABLE COPY